


# Microlens array 18-00087



#### **Features and Advantages**

Precision etched microlens array for fiber optic collimation and refocusing applications. Low pointing error and minimal optical phase front distortions enabled by wafer-level manufacturing.

\* Product picture & drawing only for reference.

### **Product Specifications**

Specification Data	Unit	Value
Material		Fused Silica
Length (L)	mm	5 ± 0.05
Width (W)	mm	5 ± 0.05
Center thickness (T)	mm	0.9 ± 0.01
Optical effective area	mm	ф0.220
Lens radius of curvature	mm	0.350
ROC tolerance within lens array	%	5%
ROC tolerance between parts	%	5%
Pitch (P)	mm	0.250
Design wavelength		

EFL


No anti-reflective coating

Product description

FS\_Sph\_Hex\_P0.25\_R0.35\_t0.9\_1\_001

1

## Product Drawing (mm)



#### Rev 01 | Updated April 29, 2024

All rights reserved. Product specifications and descriptions are subject to change. All our products are patent pending. Please contact our sales representatives for complete details.
Focuslight Switzerland SA
Focuslight (DG) Microoptics Co. Ltd.
Address: No. 49, Jingyi Road, Dongcheng Street, Dongguan City, Guangdong Province, China

Tel: +4132 566 44 44(CH) +86 29 8956 0050 (CN) | Email: sales@focuslight.com | Website: https://www.focuslight.com