

Fast Axis Collimator

FAC300 (BFL = 80μm)



Features and Advantages

Acylindrical lens for the collimation of the fast axis of diode lasers.

The new revision has an increased power content of >92% within ± 2.2 mrad and >94% of the energy within Gaussian distribution (negligible side peaks).

Product Specifications

Specification Data	Unit	Value
Material		S-TIH53 (Ohara)
Width (W)	mm	0.5 ± 0.05
Thickness (T)	mm	0.4 ± 0.01
Clear aperture	mm ²	$(L-0.5) \times 0.4$
Refractive index n @ 976 nm		1.814
Effective focal length (EFL) @ 976 nm	mm	0.30
Back focal length (BFL) @ 976 nm	mm	0.08
Numerical aperture (NA)		0.7
Transmission	%	> 99
Power within an angle of ± 2.2 mrad ⁽¹⁾	%	> 92
Power within Gaussian distribution	%	> 94
Surface imperfections (DIN ISO 10110-7)		5/2x0.025; C2x0.1; L2x0.025; E ⁽²⁾

Product Code	ZLE002600	ZLE002604
---------------------	------------------	------------------

Specification Data	Unit	Value	Value
Length (L)	mm	4.0 ± 0.05	3.0 ± 0.05
AR-Coating	nm	770 - 1070	770 - 1070

⁽¹⁾ Valid for an emitter-height of 1μm and no smile of the laser diode.

⁽²⁾ Chipping on short edge 0.2, chipping on long edge 0.05.

⁽³⁾ Example for customization — design, dimensions & coatings on request.

Product Dimensions (mm)

